

Peerless Pinnacle Oil Boiler Ratings

Boiler Model Number	Boiler Input ²		Heating Capacity ^{3,5} MBH	Net I=B=R Output ^{4,5} (MBH)	Seasonal Efficiency ⁵ (AFUE)
	(GPH)	(MBH)			
PO-70	0.50	70	64	56	91.7%
PO-70A ¹	0.50	70	65	56	92.0%
PO-84	0.60	84	77	67	91.3%
PO-84A ¹	0.60	84	77	67	91.8%

- 1 Models PO-70A and PO-84A designate boilers using an alternate minimum vent length of 25 equivalent feet.
- 2 Firing Rate is based on commercial standard #2 fuel oil with a heating value of 140,000 Btu/gallon. Burner input is based on a maximum altitude of 2,000 ft - for higher altitudes consult the factory.
- 3 Heating Capacity ratings are based on U.S. Government standard tests, with 13.0% CO².
- 4 The Net I=B=R Output Ratings are based on a pick-up allowance of 1.15. Consult the factory before selecting a boiler for gravity hot water installations or installations having unusual piping and pick-up requirements, such as intermittent system operation and extensive piping systems.
- 5 Heating Capacity, Net I=B=R Output, and Annual Fuel Usage Efficiency (AFUE) are based on testing required by the FTC and are 3rd Party Verified.